

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
16 December 2004 (16.12.2004)

PCT

(10) International Publication Number  
**WO 2004/109018 A1**

(51) International Patent Classification<sup>7</sup>: **E01D 21/00**

(21) International Application Number:  
PCT/PT2004/000011

(22) International Filing Date: 3 June 2004 (03.06.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
102968 N 6 June 2003 (06.06.2003) PT

(71) Applicant and

(72) Inventor: **PACHECO, Pedro, Álvares, Ribeiro do Carmo** [PT/PT]; Rua Doutor Manuel Rodrigues de Sousa, 21, 2º Esquerdo, Matosinhos, P-4450-181 PORTO (PT).

(74) Agent: **DURÃES ROCHA, Manuel**; Cabral Cunha Ferreira & Associados, Lda, Av. Conselheiro Fernando de Sousa, 11, Edifício Conselheiro 15º, P-1070-072 LISBON (PT).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


— of inventorship (Rule 4.17(iv)) for US only

Published:

— with international search report

[Continued on next page]

(54) Title: GANTRY WITH AUTO-ADJUSTING PRESTRESSING



(57) Abstract: The present invention refers to a gantry for use in the construction process of bridges, viaducts and other structures, said gantry being equipped with a system that automatically adjusts the prestressing of the said gantry's structure in accordance to the external actions being applied on it when loadings occur. The adjustment of the prestressing is achieved through the use of at least one sensor (2) that monitors the structure, said sensors conveying those measurements to a controller (6), said controller (6) being then capable of activating at least one actuator which alters the tension of the structure's prestressing cable or cables. Amongst the many advantages of the present invention, one is the possibility of applying a large amount of prestressing without this implying undesirable deformations in the main structure (1) when exterior loads are not applied.

WO 2004/109018 A1



*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*